L24 ANSWER 17 OF 26 WPINDEX (C) 2003 THOMSON DERWENT
AN 1981-93990D [51] WPINDEX
TI Negative electrode mfr. for alkaline storage battery - by mixing zinc powder, electrolyte-soluble paste, e.g. of carboxymethyl cellulose, **stearate** and alkali electrolyte in a bag.
DC A85 L03
PA (MATU) MATSUSHITA ELEC IND CO LTD
PI.B JP 56143667 A 19811109 (198151)* 2p
PRAI JP 1980-45908 19800407
PNC 1
CYC 1
AB JP 56143667 A UPAB: 19930915
Method comprises (1) placing zinc powder, an electrolyte- soluble paste and a **stearate** in amt. of below 1 wt.% in a bag, (2) adding an alkali electrolyte into the bag and (3) mixing the zinc powder, paste and electrolyte in the bag to form a shaped paste negative **electrode**. The **zinc** powder is uniformly dispersed in the electrode. Specifically, the paste is carboxymethyl cellulose, sodium polyacrylate or polyethylene oxide.

In an example, carboxymethyl cellulose paste, zinc powder (100 wt. pts.) and **stearate** (0.5 wt. pt.) were mixed in a bag of polypropylene non-woven cloth. Then 45% KOH soln. was added to the bag to form a paste electrode. The bag was placed on the separator of an alkaline storage battery comprising also a positive electrode and KOH soln. electrolyte in an iron case.
FA AB
FS CPI

Ref. No. 8